

UBERLUB ATF+ IV SYNTHETIC BLEND AUTOMATIC TRANSMISSION FLUID

UBERLUB ATF+ IV is a synthetic fluid exclusively designed with advanced multi-vehicle additive technology to serve a broad range of vehicles by removing the limitations of conventional Dexron® II/III/ MERCON® multi-vehicle formulations.

It is formulated with selected high viscosity index synthetic base stocks and latest additive technology available allowing very high performance needed for the demanding requirements of passenger cars automatic gearboxes.

CHARACTERISTICS (TYPICAL VALUES)

UBERLUB ATF+ IV	IV			
Specific Gravity @ 15°C	0,853			
Flash Point °C.	215			
Viscosity cSt @ 100 °C	7,24			
Viscosity cSt @ 40 °C	38,1			
VI	157			
Pour Point, °C.	-36			
COLOR	RED			

The values given above are due to research and development studies.

There may be slight transitions from production to production properties.

Health, Safety and Environmental Information

The product is not expected to cause adverse effects on human health during the period of use in accordance with the instructions for use and the recommendations for forwarding the Safety Data Sheet (MSDS). It is recommended to use child protective equipment with constant consultation with the product. Used oils should not be consumed and poured into waste water channels. Used products T.C. It should be taken back or exceeded as specified in the Waste Oil Control Regulation of the Ministry of Environment and Forestry.

0264 275 8649

www.uberlub.com.tr

Hanlı Merkez Mah. 22 Nolu Sk. No: 43 / Z1 Arifiye / Sakarya



UBERLUB ATF+ IV SYNTHETIC BLEND AUTOMATIC TRANSMISSION FLUID

PROPERTIES AND PERFORMANCES

- Extended protection Wear protection, better shear stability and oxidation resistance in hot temperatures, key factors to prolong the transmission system life.
- Transmission cleanliness Lower deposits and prevents harmful acid formation to improve the overall cleanliness of the system.
- Optimized drain intervals Superior control of sludge, varnish, rust, corrosion and other harmful deposits to ensure maximum fluid life.

INTERNATIONAL SPECIFICATIONS

- TOYOTA ATF Type T-IV
- TOYOTA ATF Type T-III
- TOYOTA ATF D-III
- TOYOTA ATF D-II
- TOYOTA JWS 3309
- LEXUS JWS 3309
- DAIHATSU AMMIX ATF D-II
- DAIHATSU AMMIX ATF D-III SP
- GM JWS 3309
- SCION (all vehicles)
- GM 9986195
- GM TASA
- GM DEXRON -II,
- GM DEXRON -IID
- GM DEXRON -IIE
- GM DEXRON -IIIG
- GM DEXRON -IIIH



0264 275 8649



www.uberlub.com.tr



Hanlı Merkez Mah. 22 Nolu Sk. No: 43 / Z1 Arifiye / Sakarya