EMEK
PETROL ÜRÜNLERİ TİC. ve SAN. LTD. ŞTİ.
Hanlı Merkez Mh. 22Nolu Sok. No43/Z1 Arifiye/SAKARYA
Tel: 0264 275 86 49 · Fax: 0264 291 42 81
info@excelloil.com · www.excelloil.com

PRODUCT DATA SHEET

UBERLUB ATF DEXRON SERIES
AUTOMATIC TRANSMISSON FLUID

UBERLUB ATF DEXRON SERIES is a automatic transmission fluids especially designed to meet the service requirements of a wide variety of applications. Produced for new generation, electronically controlled transmission systems.

CHARACTERISTICS (TYPICAL VALUES)

UBERLUB ATF DEXRON SERIES	II	III	VI	
Specific Gravity @ 15°C	0,870	0,868	0,845	
Flash Point °C.	210	220	205	
Viscosity cSt @ 100 °C	7,5	7,3	5,95	
Viscosity cSt @ 40 °C	40	38	29	
VI	157	160	155	
Pour Point, °C.	-35	-36	-40	

The values given above are due to research and development studies.
There may be slight transitions from production to production properties.
Health, Safety and Environmental Information
The product is not expected to cause adverse e ects on human health during the period of use in accordance with the instructions for use and the recommendations for forwarding the Safety Data Sheet (MSDS). It is recommended to use child protective equipment with constant consultation with the product. Used oils should not be consumed and poured into waste water channels. Used products T.C. It should be taken back or exceeded as speci ed in the Waste Oil Control Regulation of the Ministry of Environment and Forestry.

0264 275 8649
www.uberlub.com.tr
Hanlı Merkez Mah. 22 Nolu Sk. No: 43 / Z1 Arifiye / Sakarya

EMEK
PETROL ÜRÜNLERİ TİC. ve SAN. LTD. ŞTİ.
Hanlı Merkez Mh. 22Nolu Sok. No43/Z1 Arifiye/SAKARYA
Tel: 0264 275 86 49 · Fax: 0264 291 42 81
info@excelloil.com · www.excelloil.com

PRODUCT DATA SHEET

UBERLUB ATF DEXRON SERIES AUTOMATIC TRANSMISSON FLUID

PROPERTIES AND PERFORMANCES

- Extensive protection against wear, corrosion and foaming .
- It provides excellent protection against rust and corrosion.
- Very good lubricating properties even at low temperatures in winter.
- Excellent oxidation stability.
- Very low flow point.

INTERNATIONAL SPECIFICATIONS

GM	MB
Dexron IIIH Dexron IID Type A Suffix A GM Dexron V Ford MERCON® Allison C-4 Voith H55.6335 ZF TE-ML-02F, 03D, 04D, 09, 11B, 14A, 17C CAT TO–2 MAN 339 TYP Z1, V1 Ford Mercon LV	MB-Approval 236.1, 236.5

0264 275 8649
www.uberlub.com.tr
Hanlı Merkez Mah. 22 Nolu Sk. No: 43 / Z1 Arifiye / Sakarya