

UBERLUB ULTRA FULL SYNTHETIC SERIES ENGINE OILS

UBERLUB ULTRA FULL SYNT SERIES are formulated with new technology high quality full synthetic oils. Those products have a special quality additives for the protect engines. It designed for gasoline and diesel cars. These high performance motor oils are engineered and formulated with HIGH GERMAN QUALITY. These high quality motor oils also help to provide better emission control, increased fuel economy and reduced engine wear and piston deposits. They are designed to lubricate and protect well outside of the range of conventional motor oils and are compatible with a variety of different fuels including competition fuels.

Outstanding protection against wear, reduces oil and fuel consumption and ensures fast oil penetration of the engine. Oil change intervals of up to over than 35.000 km are thus possible, depending on the manufacturer's -specifications. These high performance motor oils are engineered and formulated to meet API SP / ILSAC GF-6A and meets most European ACEA specifications.

CHARACTERISTICS (TYPICAL VALUES)

UBERLUB ULTRA FULL SYNT SERIES	SAE 5W-30	SAE 5W-40	SAE 5W-20	SAE 0W-20
Specific Gravity @ 15°C	0.850	0.860	0.845	0.845
Flash Point °C.	220	220	220	220
Viscosity cSt @ 100 °C	11.25	14.5	6,8	6,8
Viscosity cSt @ 40 °C	65	91	35	35
VI	168	166	157	157
Pour Point, °C.	-42	-42	-42	-42
TBN (D-2896)	14	14	14	14

The values given above are due to research and development studies.

There may be slight transitions from production to production properties.

Health, Safety and Environmental Information

The product is not expected to cause adverse effects on human health during the period of use in accordance with the instructions for use and the recommendations for forwarding the Safety Data Sheet (MSDS). It is recommended to use child protective equipment with constant consultation with the product. Used oils should not be consumed and poured into waste water channels. Used products T.C. It should be taken back or exceeded as specified in the Waste Oil Control Regulation of the Ministry of Environment and Forestry.

0264 275 8649

www.uberlub.com.tr

Hanlı Merkez Mah. 22 Nolu Sk. No: 43 / Z1 Arifiye / Sakarya

UBERLUB ULTRA FULL SYNTHETIC SERIES ENGINE OILS

PROPERTIES AND PERFORMANCES

- High abrasion resistance.
- Fuel saving because of easy running characteristics.
- Excellent detergent and dispersant characteristics.
- Prevention of black sludge creation.
- Long endurance because of high oxidation stability.
- Excellent cold start performance.
- Very good viscosity temperature behaviour.
- Low evaporation.
- Suitable for catalysts.

INTERNATIONAL SPECIFICATIONS

API

SP, SN PLUS, SM,
SL, SJ SG, SF
SB, CF/CF-2
5W-30 DEXOS 2
SN
5W-40 DEXOS 2
SN

CUMMINS

GF-5 (0W-20,
0W-30,
0W-40, 5W-20,
5W-30,
10W-30, 15W-50)
GF-4 /
GF-3 / GF-2

ALLISON

C-4, C-3
MIL-PRF-2104G (AA52306)
MIL-L-2104-B
MIL-L-46152

MB

MB 229.1
MB 229.5
5W-30
MB 229.31
MB 229.51
5W-30 DEXOS 2
MB 229.51
MB 229.31
MB 229.52
5W-40
MB 229.31
MB 229.51

VOLKSWAGEN

VW 502.00
VW 505.00
VW 503.00
VW 505.01
VW 506.00
5W30
VW 507.00
5W-30 DEXOS 2
VW 502.00, 505.01
5W-40 DEXOS 2
VW 502.00
VW 505.01

ACEA

A3/B4, A3/B3
A5/B5, A1/B1
C4, C3, C2, C1
5W-30 DEXOS 2
C3
5W-40 DEXOS 2
C3

MIL

MIL-L-2104-B
MIL-L46152

ILSAC

G F - 6 A
GF-5 F-4
GF-3 /
GF-2 GF-1

RENAULT

5W-30 DEXOS 2
RN 0700
5W-40 DEXOS 2
RN 0700
RN 0710



0264 275 8649



www.uberlub.com.tr



Hanlı Merkez Mah. 22 Nolu Sk. No: 43 / Z1 Arifiye / Sakarya